

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 August 2005 (04.08.2005)

PCT

(10) International Publication Number
WO 2005/070720 A1

(51) International Patent Classification: **B60N 2/44**

(21) International Application Number:
PCT/KR2004/002389

(22) International Filing Date:
15 September 2004 (15.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0004720 26 January 2004 (26.01.2004) KR

(71) Applicant and

(72) Inventor: **KIM, Tae-Sook** [KR/KR]; 201-801, Lucky
Apt., 911, Mandeok 3-Dong, Buk-Gu, Busan 616-788
(KR).

(74) Agent: **KIM, Young-Ok**; 1242-7, Yeonsan 5-Dong,
Yeonje-Gu, Busan 611-085 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: BUFFER CUSHION FOR AUTOMOBILES



(57) Abstract: The present invention discloses a buffer cushion for automobiles including: a main air chamber (2) having a size corresponding to the sizes of the automobile seats; an auxiliary air chamber (3) having a relatively smaller size than the main air chamber (2); an interconnecting chamber (4) formed integrally with the main air chamber (2) and auxiliary air chamber (3) for communicating the main air chamber (2) and the auxiliary air chamber (3) with each other to allow air injected into the buffer cushion to freely move between the main air chamber (2) and the auxiliary air chamber (3); and adjusting means (5) that is mounted on the auxiliary air chamber (3) for buffering the impact applied to the main air chamber (2) and adjusting a buffering force when the impact is applied to an automobile seat in upward and downward directions.

WO 2005/070720 A1